Carlson Software Manuals

Looking for Carlson Software manuals? Prior to the 2010 release, Carlson included printed manuals with your purchase and, in addition, the manuals have always been available to print for yourself from the Help files.

With the 2010 release, Carlson "opened" a storefront on the self-publishing site called Lulu.com. You can order 2009 and 2010 Carlson Software manuals here http://stores.lulu.com/carlsonsw.

Originally posted on **Carlson Connection** by Jennifer Dibona

Export IntelliCAD or AutoCAD DWG files to Google Earth

I've recently started using a very cool feature in Carlson Software. The bad thing... it was in the 2009 version and I didn't even realize it!

I had no idea exporting our DWG files from IntelliCAD or AutoCAD out to Google Earth was so easy.

- 1. Download and install Google Earth. You can download it here: http://earth.google.com/
- 2. Open any one of your project DWG files that has been positioned at its correct state plane coordinate system.
- 3. In Carlson, go to Settings -> Drawing Setup and then select the correct **Projection** and correct **Zone** for the project site. If you're not sure of the **Projection**, try

using "State Plane 83". This will work for most systems.

Drawing Setup				
Scale and Size Settings				
Find the second seco				
C Metric 1m=?m				
Horizontal Scale: 50.0				
Symbol Plot Size: 0.0800 Drawing Units: 4.0000				
Test Plot Size: 0.0900 Drawing Units: 4.0000				
Line Type Scaler: 0.5000 LTSCALE: 25.0000				
Angle Mode				
Bearing C Azimuth C Gon C Other				
Coordinate System				
System				
C Grid @ Local Define Localization				
Projection State Plane 83 English Units US Feet				
Zone GA West Value Lat/Lon Datum WGS84 V				
Project Scale Factor: 1.00000000000				
Distance Scale Factor for Labels and Reports				
Report Scale Factor: 1.000000000000 Calculate				
DK. Cancel Set Paper Help				

- 4. Next, go to File -> Polyline File -> Write Polyline File. When prompted for "Polyline File Format", type "G" for Google. You will be prompted to specify a new filename and save location for a "Google Earth File to Write (.kml)".
- 5. You will then be prompted to select the entities that are to be exported out to the .kml file and viewed in Google Earth. After selecting the entities, press Enter. For this exercise, we only want to see the drawing entities in 2D, so press "N" for "No" when prompted to "Use elevation from drawing in Google Earth [Yes/<No>]?"
- 6. Finally, you are then prompted "Would you like to display the file in Google Earth now [<Yes>/No]?". Press "Y" for "Yes". Google Earth should automatically launch and zoom into the project location.

In the example shown below and pointed out with arrows, notice how closely the new roads and designed turn lanes match up to the existing roadway. Also, you can see the designed graded slopes perfectly avoiding the tank that is to be preserved during construction. Not too shabby... This feature is available in all of the Carlson Desktop products: Carlson Civil, Survey, Hydrology, Construction and TakeOff.

Look for a future post on bringing Google Earth surface data into Carlson Software. Hint: It's easy too!

Originally posted on Carlson Connection by Jennifer Dibona

Carlson 2010 Preview – CAD Standards

The new CAD Standards feature included in Carlson is one of the most time-saving features to come along in a long time. This feature is a collection of commands allowing you to create, manage and draw standardized Symbols, Linework and Annotation entities that are stored in a Standards Database file.

Carlson includes two Standards Database files (.sdb) with the installation: the Carlson_NCS_SurveyCivil.sdb which is a fully populated database based on the US National CAD Standard and empty.sdb which is a functional, but empty, database with which to start a new Standard Database.

Updates and additions to the .sdb files provided by Carlson Software will be posted to this website: www.carlsonsw.com/cadstandards.html.

You can click this link to view a webinar introducing the new feature.

The CAD Standards interface (loaded with the

Carlson_NCS_SurveyCivil database) is shown here:

IMAGE!

Carlson Webinars – BIM, GIS and CAD Standards

Carlson Software recently asked Felicia and me to present webinars on topics we have particular interest in or specialize in.

Felicia's webinar on BIM, GIS and Carlson Software can be viewed here: BIM, GIS and Carlson Software Webinar

My webinar on CAD Standards can be viewed here: CAD Standards for Carlson Software with AutoCAD or IntelliCAD

Originally posted on **Carlson Connection** by Jennifer Dibona

Carlson 2010 Sneak Peek

The highly anticipated Carlson 2010 release offers clients hundreds of new or improved features from that found in Carlson 2009 and continues Carlson Software's track-record of delivering responsive solutions to client-requested technology needs.

Carlson-IntelliCAD GIS Starter Kit from ESRI

Those currently using Carlson with IntelliCAD are eligible for a new "GIS Starter Kit" from ESRI. The Kit includes:

- ArcGIS ArcView desktop software
- A copy of the book A to Z GIS: An Illustrated Dictionary of Geographic Information Systems
- A copy of GIS Tutorial: Workbook for ArcView 9, Third Edition
- A 10% discount for the ESRI Survey & Engineering GIS Summit (\$325 - standard registration price)

To take advantage of the offer, call 1-800-GIS-XPRT (1-800-447-9778) and request the **Carlson-IntelliCAD GIS Starter Kit** and **please have your Carlson Serial Number available**.

You can read more about ESRI's commitment to survey and engineering services by visiting http://www.ESRI.com/engineering.

Originally posted on **Carlson Connection** by Jennifer DiBona

Ribbon vs. Menu… Your

preference is??

I was reading a recent AP article that was similar to the article entitled Meet Microsoft's antidote to Vista and saw the following:

You probably don't know her name, but if you're using Office 2007, the sleeper hit of the Vista era, you're already familiar with Larson-Green's work.

She was the one who banished the familiar system of menus on Word, Excel and other programs in favour of a new "ribbon" that shows different options at different times, depending on what a user is working on.

Hmmm... I'm wondering if she'd be willing to re-think that decision?

I'm not sure what it is about the ribbon interface but I cannot seem to get used to it. I've tried... I mean *I've really tried* to be productive with the Office 2007 ribbon but continually find myself wasting lots of time searching for a particular command whose location I could find instantly in the traditional pulldown menu system used in Windows and Office applications for the past +15 years. The article also said:

"We want to reduce the amount of thinking about the software that they have to do, so that they can concentrate all their thinking on the task they're trying to get done," Larson-Green said in an interview.

The task I'm trying to get done?? I'm trying to figure out where all my favorite old commands went for getting my work done. I'm finding that I'm spending **more** time thinking and searching for commands and having less time for the task(s) I'm trying to get done. Don't even get me started on the new default file formats for Office files (*.docx, *.xlsx, *.accdb, *etc*) and having to Save As for those who haven't adopted Office 2007 and later.

Side note observation... I wonder how soon it will be until Autodesk decides to release a *.dwgx file format? Perhaps the Open Design Alliance should beat them to the punch.

According to the frequently changing Wikipedia write-up on ribbons:

Microsoft has started the process of acquiring a patent on the ribbon user interface concept^[2] and licenses the ribbon design to third-party developers royalty-free, as long as the user interface conforms to the Microsoft's design guidelines and they can get an approval from Microsoft. The ribbon design guidelines are confidential and an evaluation copy is only available when a non-disclosure agreement has been signed.

The Ribbon has been licensed by Autodesk for AutoCAD 2009...

My fear is that when I eventually have to migrate out of AutoCAD 2008 (I'm running the ribbon-less AutoCAD 2008 and IntelliCAD and haven't even looked at AutoCAD 2009/2010), I'll be too far behind the 8-ball. Maybe I'm too grounded and comfortable with pull-down menus. I still prefer Windows XP over Vista and suspect I'd prefer pull-down menus in my CAD product like many of comments left at AutoCAD 2009 — How do you use the Ribbon? blog. Perhaps it is time to accept the fact that ribbons are likely here to stay. However, if my CAD productivity takes a hit due to the migration to ribbons like my Office productivity took a hit, I suspect I'm "going to have some 'splainin' to do." Personally, I'd love to have a one-to-one chat with Julie Larson-Green (*a.k.a.* "Microsoft's antidote to Vista") to learn

why throwing away +15 years of interface familiarity is/was a good idea.

What do you think?

[polldaddy poll=1552888]

Originally posted on Carlson Connection by Ladd Nelson

Carlson + ESRI = Wow!

So, how cool is this?

At the Carlson User Conference this week in Lexington, KY, Brent Jones of ESRI announced a new grant program in coordination with Carlson Software. The program will bring ESRI products to every IntelliCAD-based Carlson program.

Speaking with Brent on Tuesday, he said that a few of the details have yet to be worked out, but Carlson IntelliCAD users should be hearing details in about a month.

Originally posted on **Carlson Connection** by Jennifer Dibona

Brent Jones of ESRI discusses

'Why GIS Needs Surveyors'

Combining all the GIS and land development technologies that exist today is what Brent Jones suggested surveyors do in his keynote address to the attendees at the 2nd annual Carlson User Conference. Jones, PE, PLS, is the Survey, Cadastre, and Engineering Industry Manager for ESRI, which designs and develops the world's leading geographic information system (GIS) technology.

To help surveyors accomplish this, Jones announced an upcoming grant program to be offered by ESRI for every Carlson IntelliCAD user. "ESRI is very supportive of Carlson's development on IntelliCAD and we want to support your users," said Jones of this specialized grant program being developed exclusively for Carlson IntelliCAD users. "We want to help surveyors leverage their existing resources to help in the GIS market." With this offer Carlson IntelliCAD users will be able to access GIS technology and jump-start a GIS practice. Read More

Originally posted on **Carlson Connection** by Karen Cummings

How Does Carlson Support Their Users? Ask David Farina

I'm going to post a LONG email stream between one of my clients, David Farina, Bruce Carlson and Dave Carlson. You can see the new feature that David requested and Bruce and Dave's responses. David received a "development" version of the new features approximately a week after submitting this request.

I asked him for a statement describing his experience with Carlson:

Recently I found that the Time of Concentration input boxes were inadequate under the hydrology portion of Carlson Civil Suite so I emailed a description of the problem to them. I was very impressed to get a phone call the same day. They discussed the problem with me and had a revised program update to me in under a week. I've been emailing Autodesk for over a year on problems with Civil 3D and never heard a peep. Needless to say I'm very happy with the customer service I have received from Carlson thus far.

Here is the original question from David Farina on March 4, 2009:

Jennifer,

I was going through a mock project to learn the hydrology part of Carlson and noticed a critical deficiency in Time of Concentration input. The review agencies around here want to see the TR-55 method. First, the TR 55 minimum sheet flow needs to be 100' instead of 300'. They recently changed it per the TR-55 Web site. Second, I don't think I've ever had a project where you didn't have to split one of these flow types into 2 or more mannings roughness areas.

For example: a flow path that starts on dense grass for 50' then passes over asphalt for 75' and back to grass for 200' would need to be calculated as follows:

Sheet flow 50' Grass -> Sheet flow 50' Asphalt -> Shallow Concentrated flow 25' Paved -> Shallow Concentrated flow 200' UnPaved.

But as you can see the Carlson input only allows for one entry

per flow type.

Sheet Flow	Shallow Co	oncentrated Flow Cha	nnel Flow
Manning's n		0.240	Select
Two-yr 24-hr	Rainfall	3.59	in
Flow Length		100.00	ft
Land Slope		2.00	%
Time of Concentration		0.225	hr
		13.473	min

heet Flow Shallow C	oncentrated Flow	annel Flow
Surface Description	⊙ Unpaved	
Flow Length	225.00	ft
Land Slope	2.00	%
Time of Concentration	0.027	hr
	1 643	min

Below is the Intellisolve version: Notice the A, B C

Sheet Flow	A	В	С		Channel Flow	A	в	С
Manning's n-value =	0.24 💌	0.011 🔽	0.011 💌	Q	X-sectional area (sqft) =			
Flow length (ft, 300 max.) =	50	50			Wetted perimeter (ft) =			
Two-yr 24-hr rain (in) =	3.59	3.59			Channel slope (%) =			
Land slope (%) =	2	2			Manning's n-value =	0.015 💌	0.015 🐱	0.015 🔽 🤇
Sheet flow time =	7.74	0.66	0.00		Flow length (ft) =			
Shallow Concentrated FI	DW				Channel flow time =	0.00	0.00	0.00
	A	В	С					
-low length (ft) =	25	200			Shee	t flow time =	= 8.40 min	
Watercourse slope (%) =	2	2	1		Shallow (conc. flow ti	me = 1.61 m	in
watercourse slope (vs)	2	4			Chann	nel flow time	= 0.00 min	
Surface description =	Paved 💌	Unpave	 Paved 	~	Time o	of conc., Tc	= 10.0 min	

There is a 5.1 minute difference in TC results which results in a 2 CFS difference in the 100yr example below:

Method SCS Triangu	ular 🔽		Rainfall		
SubBasin		Storm Type	II - 24hr	~	
Area Units	Miles 🔿 Asses		Return Period	100 Year	~
	Miles O Acres		Rainfall Depth	9.43	in
Urainage Area	1.8498968	Select	Time Increment	0.03	hr
Runoff Curve Number	83.00		Peak Attenuation Factor	484	-11
Time of Concentration 0.17 hr Base Flow 0.00 cfs		hr	r Calculation	1.2.7	0
		cfs		IG	60
Antecedent Moisture 0	Condition ③ 3	Time to Peak 12.0 Volume 1.29	17 h 17 a	r cre-ft	

Method	SCS Triangu	ular 💊		Rainfall		
SubBasin			Storm Type	ll - 24hr	*	
Area Uni	ts O Se	Miles 💿 Acres		Return Period	100 Year	~
Desirence			·	Rainfall Depth	9.43	in
Drainage Area Runoff Curve Number		1.8498968	Select	Time Increment	0.03	hr
		83.00	Peak Attenuation Factor	484		
Time of Co	ncentration	0.25	hr		1. Sec	0
Base Flow 0.00 cfs		cfs	Calculation Peak Discharge 16.3	19	ofs	
Antecede	ent Moisture (Condition		Time to Peak 121	~ ∩	hr
01	0 2	3		Volume 1.31	Ť	acre-ft

If the above example is that different then I am also concerned about how the Time to inlet is calculated in the example below:

Settings Design Analyz	ze Analyze by Hydra
Structure Actions: Add	Edit Remove
Structure Drainage Pipe Hydr	aulic Calc
Current Structure: M1	
Input Type Drainage Data	~
Area Units O Sq Ft O Sq Mile O A	cre
Drainage Area 1.3721	Pick Calc
Time to Inlet 7.1	min
Curve Number 83	Select
Pond/Swamp Adjust 1.0000	
Known Flow 0.0000	cfs 🗌 Thru Inlet
In Hydrograph	Select

Time of Concentration (SCS)) 🛛 🛛 🔀
Input values	
Select CN from I	able
Curve Number	83
Length of Flow (ft)	412.10
Average Land Slope (%)	3.59
Select Flow Line from	Screen
Output values Time of Concentration: 0.125 hrs,	7.5 mins
<u>Calculate</u> <u>R</u> eport	<u>E</u> xit <u>H</u> elp

Was the SCS method used to get the 7.1 min value?

Notice the 7.5 value in the TC dialog to the right.

This was the value if I SELECT FLOW LINE FROM SCREEN and pick the path that the dialog on the left generates.

Can I generate a report of how the time to inlet was calculated?

Maybe there can be a button next to the Time to inlet to select TR-55

Maybe Mannings coefficients can also be put into the WATERSHED->DEFINE RUNOFF LAYERS to be used for this calc as the flow path passes through each polyline area the same way Carlson already calculates the composite CN.

😺 Define	e Runoff Layers - C:R17.2\User\Rn	ı_layer.dta 🛛 🔀
Hydro Met	thod: 🔿 Rational Method 🛛 💿 SCS Meth	od
Layer	Type of Area	Runoff Curve Number
B-CONC B-FP P-Border	Paved Lots Roofs & Driveways, Soil Type B Paved Lots Roofs & Driveways, Soil Type B Open Space-Good (>75% grass), Soil Type B	98 98 61
Default Are	a Type Unassigned Area	Default Runoff Curve Number 61
Hatch All	Hatch Selected Clear Hatch	·
Add	<u>E</u> dit <u>D</u> elete <u>L</u> oad	SaveAs OK Cancel Help

Will any of this matter if we get HydroCAD and link it to Carlson?

Just food for thought.

Thank You,

David Farina

Senior Designer

I forwarded David's question onto Bruce Carlson, President of Carlson Software, and Dave Carlson, Director of Programming, and received this response from Bruce:

Folks: Excellent input—this will find its way into the next release for sure. We've spent a lot of time studying Haested and matching numbers there on pipe flows in culverts, for example, covering all conditions—but do need to put to bed Time of Concentration for approved defaults and sub-catchment conditions as they vary within a watershed area. This Intellisolve example is really helpful. Also, I took in input at Jennifer's Statesville, NC presentation Dec. 2007 that mentioned the new 100' default and also mentioned:

Using Q=CIA, there are new "rules" being published that using larger pipes or it may be larger drainage areas, there is an added multiplier in the form Q=CIA*Q1 where Q1 is a table of values. I didn't get the full details, but we need to research this.

And in storm sewer design, if we are compositing the calc of time to inlet using a "short-form" SCS-style method, based on percentage area of various land uses and associated runoff coefficients, we need to have a Report button that documents the results for full vetting and reporting out by users, and we need to incorporate an additional auto-calculated, longform TR55 time of concentration there as well that uses sheet flow, channel flow and shallow concentrated flow. One key in all this is to be able to auto-distinguish these flow types from the DTM and land uses and have the forms filled out with default values, which the user can change.

Question I'm curious about. Say you built a gentle 6'wide, 1% slope swale with 6:1 side slopes, hardly noticeable, mowable, between lots in a subdivision. Would the flow in that be treated as shallow concentrated flow or channel flow? When would one condition end and another begin, by definition, so we can get real precise on auto-calculating these using layers/land use types and DTM values?

Good stuff, and it will get done.

Bruce Carlson, PE

Pres., Carlson Software

David added the following:

I think when to use channel flow should be determined by the width of the bottom of the channel and hence how deep the channel gets on an 2yr storm 24 storm.

You could have a channel with 1:1 side slopes but if the bottom was 50' wide and the flow path started in the channel then

the first 100' would still be sheet flow in my book. Unless of course a huge amount of water was entering the channel from another basin.

I think the concentrated and channel flow times (being in the fraction of a minute range) are so small and have such a small impact on overall time

compared to sheet flow (fraction of an hour) that you could pick an arbitrary number like 5' wide bottom and smaller is channel flow and not upset the model.

Sheet flow probably makes up 80 to 90 % of overall TC if it is over grass.

Anyone disagree?

Thank You

Dave Carlson sent this on March 11, 2009

Hi David,

Here's an update to the Tc by TR-55 routine that allows

unlimited number of breakouts. This update is for Carlson 2009 on Acad 2007-09. To install, unzip and copy the arx to the Carlson2009LSP folder. Let me know if you need a different version or have more suggestions.

For the Storm Sewer Network routine, I put it on the to-do list to add a Select button next to the Tc to show the components that make up the Tc like the Select button does for CN. Also we will looks at adding Manning's n to the Define Runoff Layers for use with Tc calcs.

Thanks for the input.

Dave

Originally posted on Carlson Connection by Jennifer Dibona